



**MLFB-Ordering data:** 1LE1503-1CA63-4AA4-Z  
F74+L25

**Motor type:** 1CV3136A

Client order no.:

Item no.:

Order no.:

Consignment no.:

Offer no.:

Project:

Remarks:

U [V]	Δ/Y	f [Hz]	P		I [A]	n [1/min]	M [Nm]	NOM. EFF at ... load [%]			Power factor at ... load			I <sub>A</sub> /I <sub>N</sub> I/I <sub>N</sub>	M <sub>A</sub> /M <sub>N</sub> T <sub>f</sub> /T <sub>N</sub>	M <sub>k</sub> /M <sub>N</sub> T <sub>B</sub> /T <sub>N</sub>	IE-CL
			[kW]	[hp]				4/4	3/4	2/4	4/4	3/4	2/4				
400	Δ	50	11.00	- / -	20.00	2955	36.0	91.2	91.9	91.8	0.86	0.82	0.74	8.8	2.4	4.5	IE3
690	Y	50	11.00	- / -	11.80	2955	36.0	91.2	91.9	91.8	0.86	0.82	0.74	8.8	2.4	4.5	IE3
460	Δ	60	12.60	- / -	19.70	3560	34.0	91.0	91.5	91.1	0.88	0.85	0.78	8.7	2.1	4.6	IE3
460	Δ	60	11.00	- / -	17.60	3565	29.0	91.0	91.1	90.3	0.86	0.82	0.73	9.6	2.5	5.2	IE3
IM B3 / IM 1001		FS 132 M		80 kg		IP55		IEC/EN 60034		IEC, DIN, ISO, VDE, EN							

Mechanical data			Terminal box	
Sound pressure level 50Hz/60Hz (load)	68 dB(A)	72 dB(A)	Terminal box position	top
Moment of inertia	0.031 kg m <sup>2</sup>		Material of terminal box	cast iron
Bearing DE   NDE	6308 2Z C3	6308 2Z C3	Type of terminal box	TB1 H01
Bearing lifetime	40000 h		Contact screw thread	M4
Lubricants	Esso Unirex N3		Max. cross-sectional area	6.0 mm <sup>2</sup>
Regreasing device	No		Cable diameter from ... to ...	11.0 mm - 21.0 mm
Grease nipple	- / -		Cable entry	2xM32x1,5
Type of bearing	Preloaded bearing DE		Cable gland	2 plugs
Condensate drainage holes	Yes (standard)		<div style="border: 1px solid black; padding: 5px; text-align: center;"> <b>Special design (2)</b> </div> <p>F74 Sheet steel fan cowl</p> <p>L25 Double sides reinforced bearings for DE and NDE, Type 63</p>	
External earthing terminal				
Vibration severity grade	A			
Insulation	155(F) to 130(B)			
Duty type	S1			
Direction of rotation	bidirectional			
Frame material	cast iron			
Data of anti condensation heating	-/-			
Coating (paint finish)	Standard paint finish C2			
Color, paint shade	RAL7030			
Motor protection	(A) without (Standard)			
Method of cooling	IC411 - self ventilated, surface cooled			

Environmental conditions	
Ambient temperature	-20 °C - +40 °C
Altitude above sea level	1000 m

