Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS

Motor type : 1AV3106B **SIMOTICS GP - 100 L - IM B14 - 4p**

Client order no.	Item-No.	Offer no.
Order no.	Consignment no.	Project
Remarks		

Electrical data

Safe Area

U [V]	Δ / Y	f [Hz]	P [kW]	P [hp]	I [A]	n [1/min]	M [Nm]	η 3) 4/4	η 3) 3/4	η 3) 2/4	cosφ 3) 4/4	cosφ 3) 3/4	cosφ 3) 2/4	I_A/I_N I_I/I_N	M_A/M_N T_I/T_N	M_K/M_N T_B/T_N	IE-CL
230	Δ	50	4.00	-/-	14.00	1455	26.5	88.6	89.4	88.8	0.81	0.75	0.62	7.5	2.9	3.7	IE3
400	Y	50	4.00	-/-	8.00	1455	26.5	88.6	89.4	88.8	0.81	0.75	0.62	7.5	2.9	3.7	IE3
460	Y	60	4.55	-/-	7.90	1755	25.0	89.5	90.0	89.4	0.81	0.75	0.64	8.1	3.0	3.9	IE3
460	Y	60	3.70	-/-	6.70	1768	20.0	89.5	89.5	87.7	0.77	0.70	0.58	9.5	3.8	4.8	IE3

IM B14 / IM 3601	FS 100 L	IP55	IEC/EN 60034	IEC, DIN, ISO, VDE, EN

Environmental conditions : -20 °C - +40 °C / 1000 m

Locked rotor time (hot / cold) : 12.8 s | 19.2 s

Mechanical data

Sound level (SPL / SWL) at 50Hz|60Hz	67 / 75 dB(A) 2)	71 / 79 dB(A) 2)	Vibration severity grade	A
Moment of inertia	0.0149 kg m²		Insulation	155(F) to 130(B)
Bearing DE | NDE	6206 2Z C3	6206 2Z C3	Duty type	S1
bearing lifetime			Direction of rotation	bidirectional
L_{10mh} $F_{Rad\ min}$ for coupling operation 50|60Hz 1)	40000 h	32000 h	Frame material	aluminum
Lubricants	Unirex N3		Net weight of the motor (IM B3)	42 kg
Regreasing device	No		Coating (paint finish)	Standard paint finish C2
Grease nipple	-/-		Color, paint shade	RAL7030
Type of bearing	Preloaded bearing DE		Motor protection	(A) without (Standard)
Condensate drainage holes	No		Method of cooling	IC411 - self ventilated, surface cooled
External earthing terminal	No			

Terminal box

Terminal box position	top	Max. cross-sectional area	4 mm²
Material of terminal box	Aluminium	Cable diameter from ... to ...	11 mm - 21 mm
Type of terminal box	TB1 F00	Cable entry	2xM32x1,5
Contact screw thread	M4	Cable gland	2 plugs

Notes:

I_A/I_N = locked rotor current / current nominal
M_A/M_N = locked rotor torque / torque nominal
M_K/M_N = break down torque / nominal torque

1) L10mh according to DIN ISO 281 10/2010
2) at rated power / at full load
3) Value is valid only for DOL operation with motor design IC411

responsible dep.	technical reference	created by	approved by	
DI MC LVM		DT Configurator		*Technical data are subject to change! There may be discrepancies between calculated and rating plate values.*

SIEMENS

document type		document status	customer	
datasheet		released		
title		document number		
1LE1003-1AB62-2KA4				
	rev.	creation date	language	Page
	01	2021-11-03 15:24	en	1/1

© Siemens AG 2021

Transmittal, reproduction, dissemination and/or editing of this document as well as utilization of its contents and communication thereof to others without express authorization are prohibited. Offenders will be held liable for payment of damages. All rights created by patent grant or registration of a utility model or design patent are reserved.

Weitergabe sowie Vervielfältigung, Verbreitung und/oder Bearbeitung dieses Dokumentes, Verwertung und Mitteilung seines Inhaltes sind verboten, soweit nicht ausdrücklich gestattet. Zuwiderhandlungen verpflichten zu Schadenersatz. Alle Rechte für den Fall der Patenterteilung, Gebrauchsmuster- oder Geschmacksmustereintragung vorbehalten

Confié à titre de secret d'entreprise. Tous droits réservés.
Comunicado come secredo empresarial. Reservados todos os direitos.
Confiado como secreto de empresa. Nos reservamos todos los derechos.



Tolerance	Surface	Material	Weight	Scale
			-	mm
1LE1003-1AB62-2KA4 -	Author	Dimensional drawing Maßzeichnung		
	Creator DTK			
	Approval			
	Department			
	Change Order	MLFB	Doc Type	
SIEMENS	Doc State 11/3/21	Item No	Paper Size A3	
	Revision Index RS	Doc No	1st Language en 2nd Language de	
© Siemens AG 2018	Project No -	Ref No -	Sheet 1 of 1	