



MLFB-Ordering data: **1LE1603-2DB03-4AB4**

Motor type: **1CV3280B**

Client order no.:

Item no.:

Order no.:

Consignment no.:

Offer no.:

Project:

Remarks:

U [V]	Δ/Y	f [Hz]	P [kW]	P [hp]	I [A]	n [1/min]	M [Nm]	NOM. EFF at ... load [%]			Power factor at ... load			I _A /I _N I/I _N	M _A /M _N T _f /T _N	M _k /M _N T _B /T _N	IE-CL
								4/4	3/4	2/4	4/4	3/4	2/4				
400	Δ	50	75.00	- / -	133.00	1485	482.0	95.0	95.3	95.0	0.86	0.83	0.75	6.9	2.5	3.0	IE3
690	Y	50	75.00	- / -	77.00	1485	482.0	95.0	95.3	95.0	0.86	0.83	0.75	6.9	2.5	3.0	IE3
460	Δ	60	86.00	- / -	131.00	1785	460.0	94.5	94.7	94.2	0.87	0.85	0.77	6.8	2.5	2.9	IE2
460	Δ	60	75.00	- / -	116.00	1788	401.0	95.4	95.3	94.5	0.85	0.81	0.72	7.7	2.8	3.3	IE3
IM B3 / IM 1001		FS 280 S		570 kg	IP55	CC032A	IEC/EN 60034	IEC, DIN, ISO, VDE, EN									

Mechanical data		Terminal box	
Sound pressure level 50Hz/60Hz (load)	69 dB(A) 77 dB(A)	Terminal box position	top
Moment of inertia	1.39 kg m ²	Material of terminal box	cast iron
Bearing DE NDE	6317 C3 6317 C3	Type of terminal box	TB1 N01
Relubrication interval/quantity	30 g 30 g 8000 h	Contact screw thread	M10
Lubricants	Esso Unirex N3	Max. cross-sectional area	120.0 mm ²
Regreasing device	Yes (standard)	Cable diameter from ... to ...	34.0 mm - 42.0 mm
Grease nipple	M10x1 DIN 3404 A	Cable entry	2xM63x1,5-2xM20x1,5
Type of bearing	Locating bearing NDE	Cable gland	4 plugs
Condensate drainage holes	Yes (standard)	Special design (0)	
External earthing terminal	Yes (standard)		
Vibration severity grade	A		
Insulation	155(F) to 130(B)		
Duty type	S1		
Direction of rotation	bidirectional		
Frame material	cast iron		
Data of anti condensation heating	-/-		
Coating (paint finish)	Special paint finish C3		
Color, paint shade	RAL7030		
Motor protection	(B) 3 PTC thermistors - for tripping (standard) (2 terminals)		
Method of cooling	IC411 - self ventilated, surface cooled		

Environmental conditions	
Ambient temperature	-20 °C - +40 °C
Altitude above sea level	1000 m

