Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS

Motor type : 1CV3314D **SIMOTICS SD - 315 L - IM B3 - 8p**

Client order no.	Item-No.	Offer no.
Order no.	Consignment no.	Project
Remarks		

Electrical data

Safe Area

U [V]	Δ / Y	f [Hz]	P [kW]	P [hp]	I [A]	n [1/min]	M [Nm]	η 3) 4/4	η 3) 3/4	η 3) 2/4	cosφ 3) 4/4	cosφ 3) 3/4	cosφ 3) 2/4	I_A/I_N I_I/I_N	M_A/M_N T_I/T_N	M_K/M_N T_B/T_N	IE-CL
400	Δ	50	90.00	-/-	168.00	740	1160.0	93.4	94.2	94.3	0.83	0.79	0.70	5.8	2.2	2.5	IE3
690	Y	50	90.00	-/-	97.00	740	1160.0	93.4	94.2	94.3	0.83	0.79	0.70	5.8	2.2	2.5	IE3

IM B3 / IM 1001		FS 315 L		IP55		IEC/EN 60034	IEC, DIN, ISO, VDE, EN

Environmental conditions : -20 °C - +40 °C / 1000 m

Locked rotor time (hot / cold) : 22.2 s | 37.2 s

Mechanical data

Sound level (SPL / SWL) at 50Hz|60Hz	71 / 85 dB(A) 2)	76 / 90 dB(A) 2)	
Moment of inertia	3.1000 kg m²		
Bearing DE | NDE	6319 C3	6319 C3	
bearing lifetime			
L_{10mh} $F_{Rad\ min}$ for coupling operation 50|60Hz 1)	40000 h	32000 h	
Relubrication interval/quantity DE | NDE	40 g | 40 g 6000 h		
Lubricants	Unirex N3		
Regreasing device	Yes (standard)		
Grease nipple	M10x1 DIN 3404 A		
Type of bearing	Locating bearing NDE		
Condensate drainage holes	Yes (standard)		

External earthing terminal	Yes (standard)
Vibration severity grade	A
Insulation	155(F) to 130(B)
Duty type	S1
Direction of rotation	bidirectional
Frame material	cast iron
Net weight of the motor (IM B3)	860 kg
Coating (paint finish)	Special paint finish C3
Color, paint shade	RAL7030
Motor protection	(B) 3 PTC thermistors - for tripping (standard) (2 terminals)
Method of cooling	IC411 - self ventilated, surface cooled

Terminal box

Terminal box position	top	Max. cross-sectional area	240 mm²
Material of terminal box	cast iron	Cable diameter from ... to ...	38 mm - 45 mm
Type of terminal box	TB1 Q01	Cable entry	2xM63x1,5-2xM20x1,5
Contact screw thread	M12	Cable gland	4 plugs

Notes:

I_A/I_N = locked rotor current / current nominal
M_A/M_N = locked rotor torque / torque nominal
M_K/M_N = break down torque / nominal torque

1) L10mh according to DIN ISO 281 10/2010
2) at rated power / at full load
3) Value is valid only for DOL operation with motor design IC411

responsible dep.	technical reference	created by	approved by	
DI MC LVM		DT Configurator		*Technical data are subject to change! There may be discrepancies between calculated and rating plate values.*

SIEMENS

document type	document status	customer
datasheet	released	
title	document number	
1LE1603-3AD43-4AB4		

rev.	creation date	language	Page
01	2021-11-03 12:47	en	1/1

© Siemens AG 2021



Tolerance	Surface	Material	Weight	Scale
			-	mm
1LE1603-3AD43-4AB4 -	Author Creator DTK Approval Department	Dimensional drawing MaÇzeichnung		
	Change Order	MLFB	Doc Type /	
SIEMENS	Doc State 11/3/21	Item No	Paper Size A3	
	Revision Index RS	Doc No	1st Language en 2nd Language de	
© Siemens AG 2018	Project No -	Ref No -	Sheet 1 of 1	

Transmittal, reproduction, dissemination and/or editing of this document as well as utilization of its contents and communication thereof to others without express authorization are prohibited. Offenders will be held liable for payment of damages. All rights created by patent grant or registration of a utility model or design patent are reserved.
Weitergabe sowie Vervielfältigung, Verbreitung und/oder Bearbeitung dieses Dokumentes, Verwertung und Mitteilung seines Inhaltes sind verboten, soweit nicht ausdrücklich gestattet. Zuwiderhandlungen verpflichten zu Schadenersatz. Alle Rechte für den Fall der Patenterteilung, Gebrauchsmuster- oder Geschmacksmustereintragung vorbehalten.
Confié à titre de secret d'entreprise. Tous droits réservés.
Comunicado como segredo empresarial. Reservados todos os direitos.
Confiado como secreto de empresa. Nos reservamos todos los derechos.