




---

 PRODUCT-DETAILS

## ACS480-04-25A0-2

LV AC general purpose drive module, IEC: Pn 5.5 kW, 25 A, 200 V (ACS480-04-25A0-2)




---

**General Information**

Global Commercial Alias	ACS480-04-25A0-2
Product ID	3AXD50000217380
ABB Type Designation	ACS480-04-25A0-2
EAN	6438177513148
Catalog Description	LV AC general purpose drive module, IEC: Pn 5.5 kW, 25 A, 200 V (ACS480-04-25A0-2)
Long Description	<p>The ACS480 is a ready-made and capable package for many applications, such as compressors, fan and conveyors, in a variety of light industries, including food and beverage, logistics and warehousing, water and wastewater, and agriculture. It has all essential features built-in as standard, simplifying drive selection, and making additional hardware unnecessary. Straightforward settings menu and assistants enable fast setup, commissioning, use and maintenance. It's a great fit for variable torque and basic speed applications, where you can leverage a compact, cabinet-optimized design for a cost-effective and efficient solution.</p>

---

**Ordering**

Country of Origin	China (CN)
Customs Tariff Number	85044085
HS Code	850440-- Electrical transformers, static converters (for example, rectifiers) and inductors.- Static converters

Invoice Description	ACS480-04-25A0-2 PN: 5.5 kW, IN: 25 A
Made To Order	Yes
Minimum Order Quantity	1 piece
Order Multiple	1 piece
Quote Only	No
Selling Unit of Measure	piece

### Container Information

Gross Volume	7.871 dm <sup>3</sup>
--------------	-----------------------

### Dimensions

Product Net Weight	2.5 kg 5.512 lb
Product Net Depth / Length	208 mm 8.189 in
Product Net Height	220 mm 8.661 in
Product Net Width	172 mm 6.772 in
Package Level 1 Depth / Length	284 mm 11.181 in
Package Level 1 Height	273 mm 10.748 in
Package Level 1 Width	250 mm 9.843 in

### Technical

Number of Phases	3
Degree of Protection	IP20
Enclosure Type NEMA	Open Type
Sound dB (A)	65.80 dB(A)
Multiple Battery Information	Lithium Coin, CR2032, 220 mAh, 3 V, 1 pc, 3 g
Frequency (f)	47.5 ... 63 Hz
Frame Size	R3
Input Voltage (U <sub>in</sub> )	200 ... 240 V
Mounting Type	Module
Communication Protocol	CAN DeviceNet EtherNet/IP MODBUS Other Bus Systems PROFIBUS PROFINET IO TCP/IP
Number of Hardware Interfaces	Industrial Ethernet 0 Other 2 Parallel 0 PROFINET 0 RS-232 0 RS-422 0 RS-485 1 Serial TTY 0 USB 1
Includes	Control unit

	PC connection
Analog Inputs	2
Analog Outputs	2
Number of Digital In/Outputs	6 / 3
Output Current, Heavy-Duty Use ( $I_{HD}$ )	17.5 A
Output Current, Light-Overload Use ( $I_{LD}$ )	24.2 A
Output Current, Normal Use ( $I_n$ )	25 A
Output Power, Heavy-Duty Use ( $P_{HD}$ )	4.0 kW
Output Power, Light-Overload Use ( $P_{LD}$ )	5.5 kW
Output Power, Normal Use ( $P_n$ )	5.5 kW
Apparent Power Output	17.3 kV·A
Efficiency Level	IE2
Complete Drive Module Efficiency (61800-9-2)	

Operating Point Frequency / Current
0/25 %
0/50 %
0/100 %
50/25 %
50/50 %
50/100 %
90/50 %
90/100 %

Temperature Rating	Maximum 50 °C
--------------------	---------------

### Classifications

ETIM 8	EC001857 - Frequency converter =< 1 kV
ETIM 9	EC001857 - Frequency converter =< 1 kV

### Environmental

WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
---------------	--

### Additional Information

Product Main Type	ACS480-04
Product Name	Frequency converter

---

## Categories

---

Drives → Low Voltage AC Drives → General Purpose Drives → ACS480-04 - Drive module

